bella EXTRUDEX

PS 400 Precision saw with debris exhaustor

Technical data

Type	PS 400 (Saw)
max. sliceable profil mm	230x60
Line speed m/min	0 - 15
inst. capacity kW	2,5
min. air-pressure bar	6
air-consumption per cycle Nl	0,24
working height mm	1.000
length-stroke mm	500
capacity for servomotor for length-stroke kW	0,8
saw-motor capacity kW	1,5
saw-blade-dia. (possible up to 400 mm dia.)	300
cutting-accuracy mm (at a cutting length of 240-500 mm)	+/- 0,5
Voltage V/Hz	400/50
Length approx. mm	1.200
Width approx. mm	1.100
Height with hood approx. mm	1.600

Type	250 DLS
AC-motor kW	1,5
air-capacity max. m^3/min	30 low-pressure max. 25 mbar (250 mm WS)
with 24 V magnetic valve for connection to SPS, digital difference pressure indication with green, yellow and red LED, collecting tank as drawer, volume 60 ltr.	
Dimensions W/L/H mm	500 550 1.600

All data subject to change without notice in accordance with technical modifications!

bella EXTRUDEX

KUNSTSTOFF-EXTRUSIONSANLAGEN
PLASTICS EXTRUSION PLANTS

bella EXTRUDEX GmbH
In den Waldaeckern 16
75417 Muehlacker / Germany
Phone +49 7041 9625-0
Fax +49 7041 9625-22
info@extrudex.de
www.extrudex.de